





# FABRIC REQUIREMENTS

Blocks & Cornerstones1 Jelly RollBackground and Border:4¾ yardsBinding:¾ yardBacking:4¼ yards

\*Jelly Roll =  $40 - 2\frac{1}{2}$ " x width of fabric strips

# **Sparkle** Quilt is 65" x 65"

### **Cutting Instructions:**

(WOF = Width of Fabric, JR = Jelly Roll)

#### From the Jelly Roll:

- Select (36) JR strips for the outer block points. From each 2 ½" strip cut:
  - o (8) 2<sup>1</sup>/<sub>2</sub>" x 4<sup>1</sup>/<sub>2</sub>" rectangles (totaling 288)
  - o Cut (61) 1½" squares for Block Centers and Cornerstones from the remaining strips and leftovers.

#### From the Background and Border 1 Fabric:

- Cut (36) 2½" x WOF strips. Subcut (576) 2½" squares; draw a diagonal line from corner to corner on the wrong side of each square.
- Cut (6) 4½" x WOF strips. Subcut (144) 4½" x 1½" rectangles for block sashing strips.
- Cut (2) 9½" x WOF strips. Subcut (52) 9½" x 1½" rectangles for quilt sashing strips.
- Cut (2) 1½" x WOF strips. Subcut (8) 1½" x 9½" rectangles for quilt sashing strips.
- Cut (7) 3½" x WOF strips. Piece for length. From the long strip Subcut the following:
  - o (2) 3½" x 59½" Side Border Strips.
  - o (2) 3<sup>1</sup>/<sub>2</sub>" x 65<sup>1</sup>/<sub>2</sub>" Top/Bottom Border Strips.

#### From the Binding Fabric:

• Cut (8) 2¼" x WOF strips.

#### **Construction:**

(Use 1/4" seams. Press in the direction of the arrows in the diagrams.)

Layer a marked 2½" BG square onto the corner of a 2½" x 4½" print fabric rectangle, right sides together and edges aligned. Diagrams show accurate placement. Sew on the drawn line. Trim ¼" from the drawn line trimming excess fabric. Press to the corner.



- 2. Layer a marked 2<sup>1</sup>/<sub>2</sub>" BG square onto the opposite corner of the same print fabric rectangle, right sides together and edges aligned. Repeat stitch and flip techniques to complete (1) rectangle unit measuring 2<sup>1</sup>/<sub>2</sub>" x 4<sup>1</sup>/<sub>2</sub>".
- 3. Repeat to make (288) rectangle units using an assortment of JR prints.





- 4. Sort the rectangle units into 72 sets of (4) matching rectangle units. Make 36 sets of (8) rectangle units, each with 2 sets of (4) matching rectangle units.
- 5. Select 1 set of (8) rectangle units. Using one of each print, lay out two rectangle units as shown. Sew together. Press the seam in one direction, or press open.
- 6. Repeat to make (4) matching block quadrants measuring  $4\frac{1}{2}$ " x  $4\frac{1}{2}$ ".



- Gather (4) matching block quadrants, (4) 1<sup>1</sup>/<sub>2</sub>" x 4<sup>1</sup>/<sub>2</sub>" block sashing strips and (1) 1<sup>1</sup>/<sub>2</sub>" print fabric square. Join the parts to make three rows as shown. Press all seams to the block sashing strips.
- 8. Join the three rows to complete a block. Press the seams to the sashing strip row.
- 9. Repeat to make (36) blocks. Blocks should measure  $9\frac{1}{2}$ " x  $9\frac{1}{2}$ ".



## Quilt Assembly:

- 10. Lay out blocks in a 6 x 6 grid as shown placing (1) 1<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>2</sub>" quilt sashing strip vertically in between each block. Lay out sashing rows using (6) 1<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>2</sub>" quilt sashing strips and (5) 1<sup>1</sup>/<sub>2</sub>" print fabric squares as cornerstones. Place sashing rows in between each block row.
- 11.Sew individual block and sashing rows together horizontally. Press all seams toward the quilt sashing strips.
- 12. Sew block and sashing rows together to complete the quilt top center. Quilt top center should measure  $59\frac{1}{2}$ " x  $59\frac{1}{2}$ ".



- 13. Attach the Side Borders measuring  $3\frac{1}{2}$ " x  $59\frac{1}{2}$ ". Press outward.
- 14. Attach the Top/Bottom Borders measuring  $3\frac{1}{2}$ " x  $65\frac{1}{2}$ ". Press outward to complete the quilt top.



15.Sew the prepared 2 1/4" x WOF strips together for binding. Layer, quilt, bind. Enjoy!





@modafabrics

pinterest.com/modafabrics